

# EXCELSYS FC4000 SERIES

FC40M MEDICAL CAPACITOR CHARGING  
AND ACDC POWER SUPPLY



**FLEXICHARGE**  
by Advanced Energy

Advanced Energy's FC40M medical capacitor charging power supply, with a built in configurable ACDC power supply is designed to provide the system power needs for medical laser applications. The FC40M can provide both capacitor charging and ACDC low voltage system power due to it's unique design and intelligent control. The FC40M can be used as a standalone capacitor charger, and if needed, various low voltage modules can be added to the unit to provide further system power. This functionality provides extra flexibility to power other systems and applications. The supply can support analog and digital control using our PMBus interface.

## PRODUCT HIGHLIGHTS

### Capacitor Charger

- Up to 4000 Watts
- 0 to 1000 VDC
- Excellent pulse to pulse stability
- User power limit control
- Internal fan cooled

### ACDC Power Supply

- Up to 800 Watts
- Up to 10 isolated outputs
- Series and parallel outputs — higher voltages/currents

### Reliability

- MTBF > 900,000 hours
- Level 4 input surge protection
- 3 W, 5 V auxiliary power on system signal connector J8
- 3 W, 15 V auxiliary power on capacitor charger D-SUB connector
- Safety approved to 3000 m altitude
- 85% Efficiency

### Flexibility

- Analog and digital management — PMBus™ monitoring and control capability

## TYPICAL APPLICATIONS

### Capacitor Charger

- Medical laser application examples: Surgical lasers, laser treatment, laser aesthetic treatments

### ACDC Power Supply

- Low voltage system power
- Power for onboard computers and displays
- Pump power
- Power for cooling and heating
- Power for other treatments

## AT A GLANCE

Charger	ACDC
Power	4000 W    800 W
Slots	NA    5
Cooling	Internal fan cooled
Parameters	348 mm x 153 mm x 132 mm
Certification and Compliance	Medical
Medical	■ IEC60601-1 3rd edition, IEC60601-1-2 4th edition (EMC)

## CAPACITOR CHARGER UNIT

Capacitor Charger						
Parameter	Conditions/Description	Min	Nom	Max	Units	
Output Voltage	The output voltage is adjustable (analog or digital)	0	—	1000	VDC	
Output Power			0	—	4000	W
Output Current	The power limits the maximum output current to < 6 A for $V_{OHV}$ , ie, $I_{OHV\_Max} = P_{OHV\_Max}/V_{OHV}$ for $V_{OHV} > 275$ V	0	—	10	A	
Capacitive Loading			50	—	—	$\mu$ F
Pulse-to-Pulse Repeatability			-2	—	2	VDC
Output Voltage Adjustment Accuracy	For $V_{OHV} > 80$ V	—	—	1	%	
Output Voltage Drift with Temperature			—	—	0.02	$^{\circ}$ C
Output Power Limit Adjustment	Adjustable using 'PLim_User' according to: $P_{OHV\_Max} = 800 + 'PLim\_User' \times 85$ [W]	800	—	1650	W	
Output Power Limit Adjustment Accuracy			—	—	3	%
Turn-On Delay	Time from application of input AC to output current regulation	—	—	2,000	mS	
Enable Delay	Time from 'Inhibit' > 2 V to output current regulation	—	—	2	mS	
Disable Delay	Time from 'Inhibit' < 1 V to output current turned off	—	—	1	mS	

## MODULES

CoolX CoolMods				
Single Output Modules (1 Slot)	V <sub>nom</sub> (V)	Set Point Adjust Range (V)	I <sub>max</sub> (A)	Power (W)
CmA	5	2.5-6.0	21.0	105
CmB <sup>1</sup>	12	6.0-15.0	15.0	180
CmC	24	15.0-28.0	8.3	200
CmD	48	28.0-58.0	4.16	200
Dual Output Modules (1 Slot)				
CmG <sup>2</sup> V1	24	3.0-30.0	3.0	90
V2	24	3.0-30.0	3.0	90
CmH <sup>3</sup> V1	5	3.0-6.0	6.0	36
V2	24	3.0-30.0	3.0	90
Wide Trim Modules (1 Slot)				
CmA-W01	5	1.0-6.0	21.0	105
CmB-W01	12	1.0-15.0 <sup>2</sup>	15.0	180
CmC-W01	24	2.0-28.0	8.3	200
CmD-W01	48	3.0-58.0 <sup>3</sup>	4.16	200
High Voltage Modules (1 Slot)				
CmK	200	175-205	0.66	132

\* SEMI F47 compliant at input voltages > 180 VAC. Consult Advanced Energy for details.

<sup>1</sup> Full dynamic specifications may not be met at full load when output voltage is trimmed by above 13 V.

<sup>2</sup> For the CmG module, the max combined power of both outputs is 120 W.

<sup>3</sup> For the CmH module, the max combined power of both outputs is 100 W.

## ELECTRICAL SPECIFICATIONS

Input						
Parameter	Conditions/Description	Min	Nom	Max	Units	
Nominal Input Voltage Range	Universal Input 47 to 63 Hz		200	—	240	VAC
AC Operating Input Range			120	—	264	VAC
Input Current			—	—	27.5	A
Inrush Current	230 VAC		—	—	50	A
Power Factor	230 VAC @ full power		0.95	—	—	—
Input Fuses Rating	Dual Fused (Line and Neutral) 500 VAC		—	40	—	A
Efficiency			—	90	—	%

CoolMod Output						
Parameter	Conditions/Description	Min	Nom	Max	Units	
<b>Single Output Modules (1 Slot)</b>						
Line Regulation	From minimum to maximum rated voltage		—	—	±0.2	%
Load Regulation	For 0 to 100% load change		—	—	±0.4	%
Transient Response	For 25% to 75% load change, 0.5 A/µs: voltage deviation		—	—	±6	%
	For 25% to 75% load change, 0.5 A/µs: settling time		—	—	500	µs
Ripple and Noise	Peak-Peak, 20 MHz BW, 100 mV or % of nominal		—	—	1.25	%
Overvoltage Protection	Tracking OVP (autorecovery, % of setpoint)		103	—	125	%
	Hiccup OVP (% of maximum voltage)		107	—	160	%
Remote Sense	Maximum cable drop compensation		—	—	0.5	VDC
Rise Time	Monotonic		—	—	5	ms
Turn-On Delay	From AC Input		—	—	2000	ms
	From Global Enable		—	—	12	ms
	From CoolMod Enable		—	—	12	ms
Hold-Up Time	For nominal output voltage at full load		16	—	—	ms
Overcurrent Protection	Straight line current limit with hiccup protection at 35% Vo nom		105	—	130	%
Short Circuit Protection	Hiccup, Autorecovery		—	—	—	—
Overtemperature Protection	Autorecovery		—	—	—	—
Capacitive Load			—	—	10	mF
<b>Dual Output Modules (1 Slot)</b>						
Line Regulation	From minimum to maximum rated voltage		—	—	±0.5	%
Load Regulation	For 0 to 100% load change		—	—	±2	%
Transient Response	For 25% to 75% load change, 0.5 A/µs: voltage deviation		—	—	±10	%
	For 25% to 75% load change, 0.5 A/µs: settling time		—	—	1000	µs
Ripple and Noise	Peak-Peak, 20 MHz BW, 100 mV or % of nominal		—	—	2	%
Overvoltage Protection	Hiccup OVP (% of maximum voltage)		110	—	130	%
Rise Time	Monotonic		—	—	20	ms
Turn-On Delay	From AC Input		—	—	2000	ms
	From Global Enable		—	—	100	ms
	From CoolMod Enable		—	—	100	ms

## ELECTRICAL SPECIFICATIONS (CONTINUED)

Hold-Up Time	For nominal output voltage at full load	10	16	—	ms
Overcurrent Protection	Hiccup, Autorecovery	165	—	335	%
Short Circuit Protection	Hiccup, Autorecovery	—	—	—	—
Overtemperature Protection	Hiccup, Autorecovery	—	—	—	—
Capacitive Load		—	—	270	μF
<b>Wide Trim Power Modules (1 Slot)</b>					
Line Regulation	From minimum to maximum rated voltage	—	—	±0.25	%
Load Regulation	For 0 to 100% load change	—	—	±0.4	%
Transient Response	For 25% to 75% load change, 0.5 A/μs: voltage deviation	—	—	±6	%
	For 25% to 75% load change, 0.5 A/μs: settling time	—	—	500	μs
Ripple and Noise	Peak-Peak, 20 MHz BW, 100 mV or % of nominal	—	—	1.25	%
Overvoltage Protection	Tracking OVP (autorecovery, % of setpoint)	103	—	125	%
	Hiccup OVP (% of maximum voltage)	107	—	160	%
Remote Sense	Maximum cable drop compensation	—	—	0.5	VDC
Rise Time	Monotonic	—	—	5	ms
Turn-On Delay	From AC Input	—	—	2000	ms
	From Global Enable	—	—	12	ms
	From CoolMod Enable	—	—	12	ms
Hold-Up Time	For nominal output voltage at full load	16	—	—	ms
Overcurrent Protection	Straight line current limit with hiccup protection at 35% Vo nom	105	—	130	%
Short Circuit Protection	Hiccup, Autorecovery	—	—	—	—
Overtemperature Protection	Autorecovery	—	—	—	—
Capacitive Load		—	—	10	mF
<b>High Voltage Modules (1 Slot)</b>					
Line Regulation	From minimum to maximum rated voltage	—	—	±0.5	%
Load Regulation	For 0 to 100% load change	—	—	±1.0	%
Transient Response	For 25% to 75% load change, 0.5 A/μs: voltage deviation	—	—	±3.75	%
	For 25% to 75% load change, 0.5 A/μs: settling time	—	—	500	μs
Ripple and Noise	Peak-Peak, 20 MHz BW, 100 mV or % of nominal	—	—	1.0	%
Overvoltage Protection	Tracking OVP (autorecovery, % of setpoint)	103	—	125	%
	Hiccup OVP (% of maximum voltage)	112	—	122	%
Rise Time	Monotonic	—	—	20	ms
Turn-On Delay	From AC Input	—	—	2000	ms
	From Global Enable	—	—	30	ms
	From CoolMod Enable	—	—	30	ms
Hold-Up Time	For nominal output voltage at full load	16	—	—	ms
Overcurrent Protection	Straight line current limit with hiccup protection at 35% Vo nom	105	—	130	%
Short Circuit Protection	Hiccup, Autorecovery	—	—	—	—
Overtemperature Protection	Autorecovery	—	—	—	—
Capacitive Load		—	—	10	μF

Auxiliary Output					
Parameter	Conditions/Description		Min	Nom	Max
Auxiliary Output Voltage	Aux Voltage A		14.7	15	15.3
	Aux Voltage B		4.8	5	5.2

## ELECTRICAL SPECIFICATIONS (CONTINUED)

Load Regulation	Aux Voltage A		—	—	±2	%
	Aux Voltage B		—	—	±2	%
Line Regulation	Aux Voltage A	For ±10% change from nominal line	—	—	±0.5	%
	Aux Voltage B		—	—	±0.5	%
Ripple and Noise	Aux Voltage A	Peak-Peak, 20 MHz BW, % of nominal	—	—	1	%
	Aux Voltage B		—	—	4	%
Maximum Output Current	Aux Voltage A		—	—	0.2	A
	Aux Voltage B		—	—	0.6	A
Maximum Output Capacitive Load	Aux Voltage A	Assuming resistive load	—	—	100	µF
	Aux Voltage B		—	—	1000	µF
Output Overcurrent Protection	Aux Voltage A	Yes, hiccup with autorecovery	105	—	130	%
	Aux Voltage B		105	—	140	%
Short Circuit Protection	Aux Voltage A	Yes, hiccup with autorecovery	—	—	—	
	Aux Voltage B		—	—	—	

## Galvanic Isolation

Parameter	Conditions/Description	Min	Nom	Max	Units
Input to Output	Reinforced (2 x MOPP); contact Advanced Energy for Hi-Pot instructions	4000	—	—	VAC
Input to Case	Basic (1 x MOPP)	1850	—	—	VAC
Output to Case	Basic (1 x MOPP)	1850	—	—	VAC
Output to Output	Basic (1 x MOPP)	1850	—	—	VAC
Output to Output (Dual)	CmG, CmH V1-V2	500	—	—	VDC

## Reliability

Parameter	Conditions/Description	Min	Nom	Max	Units
MTBF	Telecordia SR-332, Issue 4	CoolPac	—	1.11	—
		CoolMod	—	0.11	—
MTBF	Telecordia SR-332, Issue 4	CoolPac	—	900,000	Hours
		CoolMod	—	—	Hours

## ELECTRICAL SPECIFICATIONS (CONTINUED)

Environmental					
Parameter	Conditions/Description	Min	Nom	Max	Units
Operating Temperature		0	—	40	°C
Storage Temperature		-40	—	85	°C
Derating	See derating curves included in the Designers Manual	—	—	—	—
Relative Humidity	Non-condensing	5	—	90	%RH
Shock and Vibration	MIL-STD-810G Method 514.6	—	—	—	—
Altitude		—	—	3000	m

EMC		
Parameter	Conditions/Description	Criteria
Radiated Emissions <sup>1</sup>	EN 55011, EN 55022 and FCC, Class A	Compliant
Conducted Emissions	EN 55011, EN 55022 and FCC, Class A	Compliant
Power Line Harmonics	EN 61000-3-2, Class A	Compliant
Voltage Flicker	EN 61000-3-3	Compliant
ESD	EN 61000-4-2, level 4, 8 kV contact, 15 kV air	A
Radiated Immunity	EN 61000-4-3, level 3, 10V/m 80-2700 MHz	A
Electrical Fast Transient	EN 61000-4-4, level 4, ±4 kV	A
Surge Immunity	EN 61000-4-5, level 4, 2 kV DM, 4 kV CM	A
Conducted RF Immunity	EN 61000-4-6, level 3, 10 Vemf 150 KHz-80 MHz	A
Power Frequency Magnetic Field	EN 61000-4-8, level 4, 30 A/m	A
Voltage Dips & Interruptions	EN 61000-4-11	A & B Compliant


<sup>1</sup> Consult AE applications for system level compliance

Standards & Directives	
Standard	Conditions/Description
Safety Agency Approvals	EN60601-1
IEC/EN 60601-1, 2005, AMD1:2012	3,000 m (9,800 ft) altitude, 100 to 240 VAC ± 10%
IEC 60601-1-2 Edition 4	IEC 60601-1-2 (2014)
Protection class	Class I
WEEE	Waste Electrical and Electronic Equipment Directive (WEEE) 2002/96/EC
ROHS	EU DIRECTIVE 2011/65/EC RoHS compliancy
REACH	Compliant

## MECHANICAL SPECIFICATIONS

Mechanical Data		
Parameter	Description	
Dimensions (L x W x H)	L x W x H	348 mm x 145 mm x 106 mm
Weight	Nominal Weight: Flexicharge + 5 x Mods	3.75 Kg
Connectors	Description	Mating Connectors (if applicable)
AC/DC Input Terminal Block	DINKLE 0168-1502	—
Main DC Output Terminal Block (CmA-CmD)	M4 Screws	—
Main DC Output Terminal Block (CmG, CmH)	Camden - CTB9350/4A	—
Output Signal Connector (CmG, CmH)	Molex - 87833-0831	—
System Signal Connector J8	Molex 87833-1031 10-way	Locking Molex 51110-1060; Non Locking Molex 51110-1050; Crimp Terminal: Molex p/n 50394 or Molex 51110-1056 which includes locking tab and polarization keying
Output Signal Connectors J1001-J1005	Molex 87833-0631 6-way	Locking Molex 51110-0660; Non Locking Molex 51110-0650; Crimp Terminal: Molex p/n 50394 or Molex 51110-0656 which includes locking tab and polarization keying
Output Sense Connectors J3	JST-S2BPH-K(LF)(SN)	JST PHR2. Crimp Terminal JST BPH-002TP.05S or SPH-002T-P.05S

## FC40M Mechanical Drawings




\*Maximum screw penetration from base does not exceed 4.5 mm.



FC40M can be mounted on its base, vertically or on its side. FC40M can also be mounted on the DIN Rail accessory (Z744).

## INTERFACE

## Input Connectors




## FLEXICHARGE™ Connectors



J8 Connector

Pin	Name	Function
1	Common	Common ground
2	SCL	Communications port
3	LV Global EN	External global enable and disable of modules
4	SDA	Communications port
5	LV Global PG	Power Good signal for all modules
6	LV AC Fail	Primary fault status in which the modules must turn off
7	LV OTP	Warning that shutdown may occur due to over temperature
8	HV AC Fail	Primary fault status in which the cap charger output must turn off
9	Fan Fail	Primary fault status in which the fan fault has occurred must turn off
10	+5V Aux	Auxiliary output_B

## INTERFACE



Connector J100m which controls slot n	
Connector	Slot
J1001	A
J1002	B
J1003	C
J1004	D
J1005	E


Note: 'm' indicates 1, 2, 3, 4, 5;

'n' indicates A, B, C, D, E

Connector J100m which controls slot n

Pin	Name	Function
1	Common	Common ground
2	PG	Power Good signal for module
3	Common	Common ground
4	EN	External global enable and disable module
5	Itrim	Connect voltage source to control level of current limit of module
6	Vtrim	Connect voltage source to control the output voltage level

### Capacitor Charger Interface Connector






J3003

J3003 Connector


Pin	Name	Function
1	Inhibit	Inhibit
2	Ptrim	Power limit adjustment
3	HV OTP	Over temperature warning
4	Imonitor	Output current sense signal
5	Vprogram	Output voltage setting
6	HV Fault	High voltage output fault detect
7	VPeakHold	Output voltage peak level
8	Vmonitor	Output voltage sense
9	+15V Aux	15 V, 3 W user bias supply
10	Not used	
11	+15V Aux	15 V, 3 W user bias supply
12	Not used	
13	End of Charge	End-of-Charge indicator
14	Earth	Earth
15	Enable	Enable

## INTERFACE (CONTINUED)

## CoolMod Connectors



## CONFIGURATION

**Configuration Example 1**

Part number FC40M1000-ACCDH-PA specifies the following product:

FC40M—4000 W IEC60601-1 approved

Max capacitor charge voltage: 1000 Volts

Slot 1: CmA, 5 V/21 A module

Slot 2: CmC, 24 V/8.3 A module

Slot 3: CmC, 24 V/8.3 A module

Slot 4: CmD, 48 V/4.16 A module

Slot 5: CmH, 5 V/6 A and 24 V/3 A dual module

Option P: Preset required. Slot 3 and Slot 4 connected in parallel



For international contact information,  
visit [advancedenergy.com](http://advancedenergy.com)

[powersales@aei.com](mailto:powersales@aei.com) (Sales Support)  
[productsupport.ep@aei.com](mailto:productsupport.ep@aei.com) (Technical Support)  
+1 888 412 7832

## ABOUT ADVANCED ENERGY

Advanced Energy (AE) has devoted more than four decades to perfecting power for its global customers. AE designs and manufactures highly engineered, precision power conversion, measurement and control solutions for mission-critical applications and processes.

Our products enable customer innovation in complex applications for a wide range of industries including semiconductor equipment, industrial, manufacturing, telecommunications, data center computing, and medical. With deep applications know-how and responsive service and support across the globe, we build collaborative partnerships to meet rapid technological developments, propel growth for our customers, and innovate the future of power.

PRECISION | POWER | PERFORMANCE | TRUST

---

Specifications are subject to change without notice. Not responsible for errors or omissions. ©2024 Advanced Energy Industries, Inc. All rights reserved. Advanced Energy® and AE® are U.S. trademarks of Advanced Energy Industries, Inc.

